

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_d \geq 0,86 \text{ (W/m}^2\text{K)}$

Consult typology, dimensions and filling

ACCUSTIC INSULATION

Panel: **80 mm**

Maximum glazing: **64 mm**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207)

Water tightness (UNE-EN 12208)

Wind resistance (UNE-EN 12210)

Reference test: window 1,20 x 2,00 m / 1 sash.

Class 4

Class 5A

Class C5

SECTIONS	Frame 80 mm Sash 80 mm
PROFILE THICKNESS	Door 2,0 mm
MAXIMUM DIMENSIONS	Width (L) = 2100 (1700* + 400) mm Height (H) = 3000 mm <small>*Measured from pivot axis</small>
MAXIMUM WEIGHT/SASH	250 Kg

Please consult regarding maximum weight and dimensions according to types.

FINISHES	<p>Colour powder coating (RAL, mottled, rough...)</p> <p>According to Qualicoat >60 microns</p> <p>Wood effect powder coating</p> <p>According to Qualideco</p> <p>Anodized</p> <p>According to Ewwa Euras Standard Class 15</p> <p>Optionally Class 20 and 25</p> <p>Optionally bicoloured</p>
----------	--

EXTRUSION ALLOY	6063 T-5
POLYAMIDE STRIP LENGTH	24 / 26 mm
GASKETS	Double gasket
OPENING POSIBILITIES	Pivoting

